

Maximum Pipe Size: 6" Inside diameter 8-1/2" Outside diameter

Specification and Data Sheet MODEL NO. 6-RAH-7 HDG/SS

- Product Name: PILLOW BLOCK PIPESTAND MODEL NO. 6-RAH-7 HDG/SS. NOTE: Pillowblock pipestands are given
 model numbers which correspond to nominal or "trade" pipe names. Model 6-RAH-7 HDG/SS. will hold all nominal or "trade"
 6" and smaller pipe sizes. The maximum outside dimension of the pipe or conduit the model 6-RAH-7 HDG/SS will hold is
 8-1/2" diameter.
- Manufacturer: MIRO INDUSTRIES, INC., 844 South 430 West, Suite 100, Heber City, Utah 84032 Phone (800) 768-6978
 Fax (800) 440-7958
- 3. Product Description: A "roller-bearing" pipe support used to support roof mounted gas pipes, electrical conduit, solar piping and other mechanical piping. Unique design absorbs thermal expansion and contraction of pipes thus preventing damage to the roof membrane. Pipes rest on a self-lubricating roller which is made of a stainless steel rod and a polycarbonate resin roller. The pipe support base and all other material are made of stainless steel or hot-dip galvanized steel. Pipestand will accommodate up to a 6" inside diameter pipe or up to 8-1/2" outside diameter pipes.
- 4. **Product Performance**: The "U" shaped cradle serves to keep the pipestand roller system directly beneath the pipe without binding and allows for some lateral expansion of the piping system. The base is gently rounded to prevent gouging with edges raised 1". Drainage ports are provided to prevent ponding within the device.
- Compatibility: Pillow Block Pipestands are recommended for use on and compatible with all current types of decking and with all commonly used built-up and single-ply roofing membranes where roof-mounted pipes occur.
- 6. Load Weight: Maximum load weight not to exceed 349 lbs. per pipestand.
- 7. **Composition and Materials**: The pipestand consists of two major components: (1) A one-piece stainless or hot-dip galvanized steel roof deck base, pipe support and adjustable roller housing, and (2) A rod made of stainless steel and polycarbonate roller which rests upon the adjustable height roller housing connected with 1/2" diameter stainless steel all thread.
- 8. **Size**: The Pillow Block Pipe Stand Model 6-RAH-7 HDG/SS is made in one standard size. The deck base is 12" x 16", has a maximum cradle width of 8-1/2", and can adjust in height from a low of 3-1/2" to a high of 7" from bottom of pipe support.
- 9. Installation: (1) Center the pipestand beneath the pipe so that the cradle allows the pipe to be squarely over and through the roller of the pipestand. (2) Adjust the pipestand to the desired height and even load with other pipestands. Make certain the roller and horizontal rod is level. (3) Set the pipe in the pipestand without dropping or causing undue impact. An additional sheet of roofing material, a MIRO Support Pad, or a MIRO Deck Plate should be installed beneath the pipestand. For built up roofs, all loose aggregate from an area 20" square should be removed from the area directly beneath the pipestand and then follow the installation directions set forth above. Care should be taken to install each pipestand so it supports a proportional and equal amount of weight at each pipestand.
- 10. **Spacing**: Manufacturer's recommended spacing is not to exceed 10 foot centers depending upon the load. Do not exceed specified load weight and make certain each pipestand is adjusted in height to even load at all pipestands. Support spacing is not to exceed the maximum spacing required in the pipe specifications where applicable.
- 11. Availability: Pillow Block Pipestands are marketed throughout the United States through representatives and distributors.
- 12. **Maintenance**: Normally maintenance is not required. Semi-annual inspection is required to check pipestand position and set pipe alignment, weight distribution and improper installation which may cause pipestand damage or failure.
- 13. **Technical Services:** Please call MIRO INDUSTRIES, INC.: (800) 768-6978 or visit our website <u>www.miroind.com</u> for technical information and for graphic and CAD drawing downloads.