S4720

NONE

APPROVED BY JM SUPERSEDED OR VOID

WE CAN ASSUME NO RESPONSIBILITY FOR USE

DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE

DRAWING NUMBER



LOCATION

WALL ACCESS COVERS

ROUND FRAME WITH SECURED COVER

FUNCTION: Used to cover cleanout plugs, valves, controls or equipment concealed in walls. The round design eliminates necessity for lining up with adjacent floors, ceilings, moldings, etc. The anchoring lugs provide easy means for securing the frame to the wall construction.

The face-of-wall cover is for tile, masonry, or dry wall construction and is usually installed on an opening provided in the finished wall.

The flush-with-wall cover is for plaster or wet wall construction and is installed during the wall construction.




Fig. 4720 FACE-OF-WALL COVER eg: 4720 (-04)*

FIG. 4720

Specify FIG.	Plug Size	B Dia.	D Dia.	
4720 (-04)	2 (51)	4 (100)	6 (150)	
4720 (-05)	3 (76)	5 1/2 (140)	7 (180)	
4720 (-06)	4 (100)	6 (150)	7 1/2 (190)	
4720 (-08)	5 (125)	8 (205)	10 (255)	
4720 (-08)	6 (150)	8 (205)	10 (255)	

*Reflects B DIA.

NOTE: Dimensions shown in parentheses are in millimeters.

REGULARLY FURNISHED:

Chrome Plated Bronze Round Frame and Secured Cover. Type of Cover as Indicated by Figure Number Selected.

VARIATIONS:

Vandal Proof Screws -U

3 Anchor Lugs Finished Wall

3/4 (19)

Fig. 4725 FLUSH-WITH-WALL COVER eg: 4725 (-04)*

FIG. 4725

Specify FIG.	Plug Size	B Dia.	C Dia.	
4725 (-04)	2 (51)	4 (100)	4 1/2 (115)	
4725 (-05)	3 (76)	5 1/2 (140)	5 3/4 (145)	
4725 (-06)	4 (100)	6 (150)	6 1/2 (165)	
4725 (-06)	5 (125)	6 (150)	6 1/2 (165)	
4725 (-08)	6 (150)	8 (205)	8 1/2 (215)	
4725 (-10)	8 (205)	10 (255)	10 1/2 (265)	

OPTIONAL MATERIALS:

Nickel Bronze Frame and Cover -NB
Polished Bronze Frame and Cover -PB

١					WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER
H G	5-21-99 2-2-99	Changed Table Changed Tables	CMD CMD	JCS BS			4720, 4725
REV.	DATE	DESCRIPTION	BY	CKD. BY			T120, T125