

## Maze Nails

## **Product Specification Sheet**

## **Hot-Dip Galvanized Flat Rubber Washer Nails**

Stock Number: R167AF

LENGTH
SHANK DIAMETER
HEAD DIAMETER
SHANK STYLE

POINT STYLE

COATING

**MATERIAL** 

**APPROX. NAILS PER LB** 

Medium Carbon Steel

2-1/2"

0.135"

.375"

Ring Thread

33 degree diamond

Double Hot-Dip Galvanized

82.0

## **Product Description**

Widely used for fastening corrugated metal roofing and siding. Also popular for aluminum and fiberglass products. Nails are double dipped in molten zinc after threading so no raw steel is exposed. EPDM rubber washers seal nail holes. Ring shanks hold tight. Available from stock in many popular colors. Call for availability. For painted nails, add \$21.45 per 50 lbs., \$2.15 per 5 lbs., \$.43 per 1 lb. Non-stocked colors require a minimum order of 200 lbs. per size and color and 100 lb. increments beyond. Most manufacturers recommend minimum nail penetration of 1" into purlin or girt.



Disclaimer: This image represents an entire series of nails, so the length may not be the exact match to the nail in this spec sheet

\*100% MADE IN THE USA\*

Generated on: 6/18/2020