



# Maze Nails

## Product Specification Sheet

### Hot-Dip Galvanized Plain Shank Asphalt & Fiberglass Shingle Nails

Stock Number: R100

<b>MATERIAL</b>	Medium Carbon Steel
<b>LENGTH</b>	7/8"
<b>SHANK DIAMETER</b>	0.121"
<b>HEAD DIAMETER</b>	.375"
<b>SHANK STYLE</b>	Smooth
<b>POINT STYLE</b>	40 degree diamond
<b>COATING</b>	Double Hot-Dip Galvanized
<b>APPROX. NAILS PER LB</b>	272.0

#### Product Description

Designed for the secure application of asphalt and fiberglass shingles on new construction and re-roofing jobs. STORMGUARD® Double Hot-Dipped Zinc-Coating provides extra corrosion-resistance in sea coastal areas. Manufactured to meet federal spec. ASTM F1667 and ASTM spec. A-153 for hot-dip zinc coating. Nails should be long enough to penetrate 3/4" into the wood deck lumber, or completely through plywood decking. All Maze Nails are 100% Made in the U.S.A. SIZES AND QUANTITIES COMMONLY USED On A New Roof – 1-1/4" - 320 nails per sq. or 1-3/4 lbs. Over An Old Roof – 1-3/4" - 320 nails per sq. or 2-1/4 lbs.



Disclaimer: This image represents an entire series of nails, so the length may not be the exact match to the nail in this spec sheet

**\*100% MADE IN THE USA\***

Generated on: 6/17/2020